

PARAMETER

Size	83mm(L)*40mm(W)*14mm(H)
Working Temperature	-25°C to 75°C
Working Voltage	9-90V

Class12. TCP/IP Built-in GSM Module


Weight 52g
Built-in Battery 250mAh

HARDWARE SPECIFICATION

Location Accuracy	<=10m	Channel	20 Class
GPS Chip	MT2503D	GPS Sensitivity	-144dBm
GSM Frequency	850/900/1800/1900MHZ	Tracking Sensitivity	-160dBm
	Hot Start<2SEC(Open Sky)	Power LED Indicator	Red
Positioning Time	Warm Start<15SEC	GPS LED Indicator	Blue
	Cold Start<38SEC(Open Sky)	GSM LED Indicator	Green
GSM Antenna	Spring Antenna		
GPS Antenna	Built-in 25mm*25mm*4mm Ceramic Antenna		

SOFTWARE SPECIFICATION

Data Upgrade Port	Not Support	ACC Detection	Support
Function Port Definition	Not Support	Geo-fence	Support
Parameter Setting	SMS Command, Platform	Cut-wire Alarm	Support
GPRS Upload	Upload Interval Every 10 Seconds	Vibration Alarm	Support
Third-party Checking	WEB/APP	Movement Alarm	Support



FUNCTION



Real-time Tracking



Remotely Cut-off Petrol/Electricity



SOS Emergency Call



Remotely Voice Monitoring



Built-in Battery



Multiple Alert Protections

APPLICATION



Car Tracking



Fleet Management



Truck Tracking